




SPECIFICATIONS	
HOUSING MATERIAL	DIE-CAST ALUMINUM ALLOY
HOUSING FINISH/COLOR	POWDER COAT/BLACK
RECEPTACLE HOUSING MAT'L/PLATING	BRASS/NICKEL
CONTACT CARRIERS MATERIAL	TPU
CONTACTS MATERIAL/PLATING	BRASS/GOLD
OPERATING VOLTAGE	300 V
OPERATING CURRENT	9.0 A PER CONDUCTOR
PROTECTION CLASS to DIN 40050	IP 67 – ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED
OPERATING TEMPERATURE	-40 to +70C (-40 to +158F)

P1 CONNECTOR




1 = + VOLTAGE
2 = N/C
3 = – VOLTAGE
4 = N/C

S0-S8 CONNECTORS




1 = + VOLTAGE
2 = N/C
3 = – VOLTAGE
4 = N/C

WIRING DIAGRAM




SOURCE DRAWING - FOR REFERENCE ONLY



REV	DESCRIPTION	BY	DATE	ECO NO.
G	ADD CE/UKCA TO CLICHE	TR	08/17/22	500000006082

RELATED DOCUMENTS
1.
2.
3.
4.

3RD ANGLE PROJECTION



THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

TURCK

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

MATERIAL

FINISH

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

DRFT IK | DATE 12/12/00

APVD | SCALE 1=2.0

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

DESCRIPTION
JBBS-25-M814

IDENTIFICATION NO.
U7805

REV
G

FILE: U7805

SHEET 1 OF 1