



SPECIFICATIONS	
HOUSING MATERIAL	DIE-CAST ALUMINUM ALLOY
HOUSING FINISH/COLOR	POWDER COAT/BLACK
RECEPTACLE HOUSING MAT'L/FINISH	STAINLESS STEEL/PASSIVATED
CONTACT CARRIERS/COLOR	TPU/BLACK
CONTACTS MATERIAL/PLATING	BRASS/GOLD
OPERATING VOLTAGE	300 V
OPERATING CURRENT	9.0 A PER CONDUCTOR
PROTECTION CLASS to DIN 40050	IP 67 – ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED
OPERATING TEMPERATURE	-40°C to +70°C (-40°F to +158°F)

P1 CONNECTOR




1 = + VOLTAGE
2 = N/C
3 = – VOLTAGE
4 = SHIELD

mini fast.

PROFIBUS-PA

S0–S8 CONNECTORS




1 = + VOLTAGE
2 = GROUND
3 = – VOLTAGE
4 = SHIELD


mini fast.

PROFIBUS-PA

WIRING DIAGRAM



SOURCE DRAWING - FOR REFERENCE ONLY



REV	DESCRIPTION	BY	DATE	ECO NO.
F	ADD CE-UKCA MARK TO CLICHE	RDS	08/18/22	50000006082

RELATED DOCUMENTS
1.
2.
3.
4.

MATERIAL

FINISH

3RD ANGLE PROJECTION

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

TURCK
3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

DRFT IK
DATE 10/11/00
APVD
SCALE 1=2.0

UNIT OF MEASUREMENT
MILLIMETER [INCH]
DO NOT SCALE THIS DRAWING

DESCRIPTION
JBBS-48-M813

IDENTIFICATION NO.
U0215-483

REV
F

FILE: U0215-483

SHEET 1 OF 1